


NOTES:

- 370EZ SLIDES ARE PROVIDED WITH A LOCK-OPEN FEATURE AND A QUICK-DISCONNECT OF THE INNER SLIDE MEMBER.
- THE SLIDES ARE NON-HANDED AND MAY BE USED AS A LEFT OR RIGHT HAND SLIDE.
- HOLES IN ADDITION TO THOSE SHOWN MAY BE IN THE SLIDE MEMBERS AT JONATHAN'S OPTION.
- USE NUMBER 8 PAN OR BINDING HEAD SCREWS FOR MOUNTING THRU THE INNER SLIDE MEMBER. USE NUMBER 8, 100° FLAT HEAD SCREWS FOR MOUNTING THRU THE OUTER SLIDE MEMBER.
- THE EZ RAIL LATCH PROVIDES A PINCH-FREE, COLORED TOUCH POINT FOR UNLOCKING THE SLIDES FOR CLOSING AND FOR DISCONNECTING THE INNER SLIDE MEMBER.
- WHEN THE INNER MEMBER IS DISCONNECTED, THE EZ RAIL LATCH LOCKS THE BALL RETAINER IN ITS FULLY FORWARD POSITION FOR PROPER ALIGNMENT WITH THE INNER MEMBER UPON REINSTALLATION.
- THE EZ RAIL LATCH ALLOWS THE INNER SLIDE MEMBER TO BE INSTALLED WITH THE CABINET SECTION FULLY CLOSED. THE INNER SLIDE MEMBERS CAN BE INSTALLED WITH A SINGLE DIRECTION CLOSING MOTION WITHOUT THE NEED TO DISENGAGE THE LOCK FORWARD MECHANISM.



ISOMETRIC REPRESENTATION

PART NO.	SLIDE LENGTH	SLIDE TRAVEL	MOUNTING HOLE PATTERN										LOAD RATING
			INNER CHANNEL			OUTER CHANNEL			PER PAIR				
SERIES	DIM. L	DIM. T	A	B	C	D	E	F	G				
370EZ-12	12	13	3.000	76.20	9.000	228.60		8.500	9.500	235	LBS	235	LBS
	304.8	330					114.30	215.90	241.30	107	KG	107	KG
370EZ-14	14	15	4.000	101.60	11.000	279.40	2.000	7.500	8.500	230	LBS	230	LBS
	395.6	381	101.60		50.80	190.50	266.70	292.10	104	KG	104	KG	
370EZ-16	16	17	4.500	114.30	13.000	330.20	3.000	8.000	9.000	215	LBS	215	LBS
	406.4	432	114.30		330.20	76.20	215.90	317.50	342.90	98	KG	98	KG
370EZ-18	18	19	5.500	139.70	15.000	381.00	3.500	8.500	9.500	200	LBS	200	LBS
	457.2	483	139.70	292.10	381.00	88.90	234.00	368.30	393.70	91	KG	91	KG
370EZ-20	20	21	6.000	152.40	17.000	431.80	4.000	11.500	12.500	195	LBS	195	LBS
	508	533	152.40	317.50	431.80	101.60	292.10	419.10	444.50	88	KG	88	KG
370EZ-22	22	23	7.000	177.80	19.000	482.60	5.000	13.500	14.500	190	LBS	190	LBS
	558.8	584	177.80	355.60	482.60	127.00	317.50	469.90	495.30	86	KG	86	KG
370EZ-24	24	25	7.500	190.50	21.000	533.40	5.500	14.500	15.500	180	LBS	180	LBS
	609.6	635	190.50	381.00	533.40	139.70	355.60	520.70	546.10	82	KG	82	KG
370EZ-26	26	27	8.000	203.20	23.000	584.20	7.000	15.500	16.500	175	LBS	175	LBS
	660.4	686	203.20	419.10	584.20	177.80	393.70	571.50	596.90	79	KG	79	KG
370EZ-28	28	29	9.000	228.60	25.000	635.00	8.000	16.500	17.500	170	LBS	170	LBS
	711.2	737	228.60	457.20	635.00	203.20	419.10	622.30	647.70	77	KG	77	KG
370EZ-30	30	31	9.500	241.30	27.000	685.80	8.500	18.500	19.500	160	LBS	160	LBS
	762	787	241.30	492.60	685.80	215.90	457.20	673.10	698.50	73	KG	73	KG

EZ RAIL LATCH

PRESS PINCH-FREE EZ RAIL LATCH HERE TO FREE THE SLIDE FOR CLOSING OR TO DISCONNECT THE INNER MEMBER.

LENGTH = $L - 1.12$
[L-3.1]2.020 MAX.
[51.3]±.02
[.51].94
[23.88]±.03
[.76].50
[12.7].41 INNER AND
INTERMEDIATE
CHANNELS
[10.4]

END VIEW

TRAVEL = $T \pm .12$
[T±.31]LENGTH = $L \pm .03$
[L±.76]

Irvine Technology Center
410 Exchange, Suite 200
Irvine, CA 92602
Tel: (714) 665-4400
Website: www.JonathanEngr.com
Engineering • Production • Integration / Subassembly • Logistics
United States • Mexico • China • Taiwan



DESCRIPTION:

SERIES

370EZ

STEEL

SERIES 370EZ

LOAD RATING: 160-235 LBS./ 73-107 KG.

DATE: 7/09

COPYRIGHT © 2009 JONATHAN ENGINEERED SOLUTIONS