



- 8 THESE SURFACES ALIGN WHEN SLIDE IS IN THE CLOSED POSITION
7. CABINET SECTION AND CHASSIS SECTION MAY BE PURCHASED SEPERATELY AND ARE INTERCHANGEABLE
- 6 AMOUNT AND LOCATION OF ROLLERS TO BE DETERMINED BY JONATHAN ENGR. SOLUTIONS
5. USE #8 100 DEG. FLAT HEAD MACHINE SCREWS FOR MOUNTING THRU SLIDE MEMBERS.
4. SLIDE LOCKS IN OPEN POSITION AND IS PROVIDED WITH QUICK DISCONNECT OF CHASSIS SECTION.
3. LEFT HAND SHOWN, RIGHT HAND OPPOSITE
2. FINISH: CHANNELS ARE ANODIZED PER MIL-A-8625, TYPE II, CLASS I. CRES PARTS ARE PASSIVATED PER SAE-AMS-2700
1. MATERIAL: CHANNELS ARE FABRICATED FROM HIGH STRENGTH ALUMINUM ALLOYS WITH A TENSILE STRENGTH OF 35,000 PSI MIN. (PER ASTM B221) COMPONENT PARTS ARE FABRICATED FROM HIGH STRENGTH ALUMINUM ALLOYS AND CORROSION RESISTANT STEEL. BALLS ARE 440 CRES.

| PART NO. | SLIDE LENGTH | SLIDE TRAVEL | CABINET SECTION |        |        |        | CHASSIS SECTION |       |        |        | LOAD RATING - PER PAIR |   |
|----------|--------------|--------------|-----------------|--------|--------|--------|-----------------|-------|--------|--------|------------------------|---|
|          |              |              | A               | B      | C      | D      | E               | F     | G      | H      |                        | J |
| 260QD-10 | 10.00        | 10.00        | 2.000           | -      | -      | 5.250  | 8.250           | 2.000 | -      | -      | 6.500                  |   |
| 260QD-11 | 11.00        | 11.00        | 2.000           | -      | -      | 6.250  | 9.250           | 2.000 | -      | -      | 7.500                  |   |
| 260QD-12 | 12.00        | 12.00        | 2.000           | -      | -      | 6.250  | 10.250          | 2.000 | 3.000  | -      | 8.500                  |   |
| 260QD-13 | 13.00        | 13.00        | 3.000           | -      | -      | 7.250  | 11.250          | 2.000 | 3.000  | -      | 9.500                  |   |
| 260QD-14 | 14.00        | 14.00        | 3.000           | -      | -      | 7.250  | 12.250          | 2.000 | 4.000  | -      | 10.500                 |   |
| 260QD-15 | 15.00        | 15.00        | 3.000           | -      | -      | 8.250  | 13.250          | 2.000 | 4.000  | -      | 11.500                 |   |
| 260QD-16 | 16.00        | 16.00        | 4.000           | 8.000  | -      | 11.250 | 14.250          | 3.000 | 5.000  | 10.000 | 12.500                 |   |
| 260QD-17 | 17.00        | 17.00        | 4.000           | 8.000  | -      | 12.250 | 15.250          | 3.000 | 5.000  | 11.000 | 13.500                 |   |
| 260QD-18 | 18.00        | 18.00        | 5.000           | 10.000 | -      | 13.250 | 16.250          | 4.000 | 6.000  | 11.000 | 14.500                 |   |
| 260QD-19 | 19.00        | 19.00        | 5.000           | 10.000 | -      | 14.250 | 17.250          | 4.000 | 6.000  | 12.000 | 15.500                 |   |
| 260QD-20 | 20.00        | 20.00        | 3.000           | 6.000  | 10.000 | 14.250 | 18.250          | 4.000 | 7.000  | 12.000 | 16.500                 |   |
| 260QD-21 | 21.00        | 21.00        | 3.000           | 6.000  | 10.000 | 15.250 | 19.250          | 4.000 | 7.000  | 13.000 | 17.500                 |   |
| 260QD-22 | 22.00        | 22.00        | 3.000           | 7.000  | 12.000 | 16.250 | 20.250          | 5.000 | 8.000  | 13.000 | 18.500                 |   |
| 260QD-23 | 23.00        | 23.00        | 3.000           | 7.000  | 12.000 | 17.250 | 21.250          | 5.000 | 8.000  | 14.000 | 19.500                 |   |
| 260QD-24 | 24.00        | 24.00        | 3.000           | 7.000  | 12.000 | 17.250 | 22.250          | 6.000 | 9.000  | 14.000 | 20.500                 |   |
| 260QD-25 | 25.00        | 25.00        | 3.000           | 7.000  | 12.000 | 18.250 | 23.250          | 6.000 | 9.000  | 15.000 | 21.500                 |   |
| 260QD-26 | 26.00        | 26.00        | 4.000           | 8.000  | 14.000 | 19.250 | 24.250          | 6.000 | 10.000 | 16.000 | 22.500                 |   |
| 260QD-27 | 27.00        | 27.00        | 4.000           | 8.000  | 14.000 | 20.250 | 25.250          | 6.000 | 10.000 | 17.000 | 23.500                 |   |
| 260QD-28 | 28.00        | 28.00        | 4.000           | 8.000  | 14.000 | 20.250 | 26.250          | 6.000 | 11.000 | 18.000 | 24.500                 |   |



Irvine Technology Center  
 410 Exchange, Suite 200  
 Irvine, CA 92602  
 Tel. (714) 665-4400  
 Fax: (714) 368-7002  
 Website: www.jonathanengr.com  
 Engineer - Production - Integration/ Subassembly - Logistics  
 United States - Mexico - China - Taiwan

|                                   |       |        |       |  |  |  |
|-----------------------------------|-------|--------|-------|--|--|--|
| TOLERANCES UNLESS OTHERWISE NOTED |       |        |       | PART NUMBER :<br><b>260QD</b>                  |  | DESCRIPTION :<br><b>ALUMINUM 260QD</b><br><b>LOAD RATING :</b> |
| .XX                               | .XXX  | ANGLES | HOLES | DATE :<br><b>10/24/11</b>                      |  |  |
| ±.01                              | ±.005 | ±1°    | ±.005 | COPYRIGHT © 2009 JONATHAN ENGINEERED SOLUTIONS |  |  |