



PART NO. SERIES LENGTH	SLIDE LENGTH	SLIDE TRAVEL	MOUNTING HOLE PATTERN				LOAD RATING
	DIM. L	DIM. T	OUTER CHANNEL A	INNER CHANNEL B C D			PER PAIR
330QD-SS-10	9.84 [250]	5.79 [147]	5.512 [140]	1.181 [30]	-	.591 [15]	-
330QD-SS-12	11.81 [300]	7.76 [197]	5.512 [140]	2.362 [60]	-	.591 [15]	-
330QD-SS-14	13.78 [350]	9.17 [233]	5.512 [140]	2.362 [60]	4.331 [110]	.591 [15]	-
330QD-SS-16	15.75 [400]	10.47 [266]	7.087 [180]	2.362 [60]	4.331 [110]	1.378 [35]	-
330QD-SS-18	17.72 [450]	11.81 [300]	9.449 [240]	2.362 [60]	6.299 [160]	1.378 [35]	-
330QD-SS-20	19.69 [500]	12.99 [330]	9.449 [240]	2.362 [60]	8.268 [210]	1.378 [35]	-
330QD-SS-22	21.65 [550]	14.41 [366]	11.024 [280]	2.362 [60]	8.268 [210]	1.378 [35]	-
330QD-SS-24	23.62 [600]	15.75 [400]	11.024 [280]	2.362 [60]	10.236 [260]	1.378 [35]	-
330QD-SS-26	25.59 [650]	17.05 [433]	12.992 [330]	2.362 [60]	10.236 [260]	1.378 [35]	-
330QD-SS-28	27.56 [700]	18.78 [477]	12.992 [330]	2.362 [60]	22.441 [310]	1.378 [35]	-

- MATERIAL: STAINLESS STEEL TYPE 300
- LUBRICATION: EXTREME PRESSURE, HI-LOW TEMPERATURE POLYMER GREASE.
- SLIDE LOCKS IN OPEN POSITION AND IS PROVIDED WITH QUICK DISCONNECT OF INNER MEMBER.
- DIMENSIONS SHOWN IN INCHES AND [MILLIMETERS]
- THIS SLIDE IS SYMMETRICAL, MAY BE USED AS LEFT OR RIGHT HAND MOUNTING UNIT.
- MARK JONATHAN NAME & PART NUMBER:
JONATHAN
330QD-SS-XX (XX=LENGTH OF SLIDE)
WW/YY (DATE CODE: WW=WEEK; YY=YEAR)
- HOLES OTHER THAN THOSE SHOWN MAY BE IN SLIDE.
- USE M4 PAN OR BINDING HEAD SCREWS FOR MOUNTING THRU THE SLIDE MEMBERS



Irvine Technology Center
410 Exchange, Suite 200
Irvine, CA 92602
Tel: (714) 665-4400
Fax: (714) 368-7002
Website: www.jonathanengr.com
Engineer - Production / Integration / Subassembly - Logistics
United States - Mexico - China - Taiwan

TOLERANCES UNLESS OTHERWISE NOTED		PART NUMBER: 330QD-SS		DESCRIPTION: STAINLESS STEEL SERIES 330QD-SS	
.XX .X .XXX .XX	ANGLE	HOLES	DATE:	LOAD RATING: 100 LBS.	
±.03 [-.8]	± 2°	±.010 [±.25]	1/11		
SHEET 1 OF 1					