



Irvine Technology Center
 410 Exchange, Suite 200
 Irvine, CA 92602
 Tel: (714) 665-4400
 Fax: (714) 368-7002
 Website: www.jonathanengr.com
 Engineer - Production - Integration / Subassembly - Logistics
 United States - Mexico - China - Taiwan



DESCRIPTION:
MATERIAL: ALUMINUM
SERIES: CMS-15

TOLERANCES UNLESS OTHERWISE NOTED		PART NUMBER: CMS-15	
.XX	.XXX	ANGLES	HOLES
± .01	± .005	± 1°	± .005
DATE: 1/11			SHEET 1 OF 1

4. LOCTITE IS APPLIED TO SCREW(S)
3. CABLE ARM IS PROPRIETARY TO JONATHAN ENGINEERED SOLUTIONS AND IS PATENT PENDING.
2. FINISH: ALUMINUM PARTS ARE ANODIZED PER MIL-A-8625, TYPE II, CLASS I. CRES COMPONENTS ARE PASSIVATED PER SAE-AMS-00-P-35.
1. MATERIAL: CABLE ARMS AND BRACKET ARE FABRICATED FROM HIGH STRENGTH ALUMINUM ALLOY WITH A MINIMUM TENSILE STRENGTH OF 35,000 PSI. COMPONENT PARTS ARE STAINLESS STEEL AND HIGH STRENGTH ALUMINUM.