



6 THESE SURFACES ALIGN WHEN SLIDE IS IN THE CLOSED POSITION.

- 5. USE #8 X 100° FLAT HEAD MACHINE SCREWS FOR MOUNTING THRU SLIDE MEMBERS
- 4. SLIDE FEATURES QUICK DISCONNECT OF CHASSIS SECTION.
- 3. RIGHT HAND SHOWN, LEFT HAND OPPOSITE.

7. WHEN ORDERING PLEASE SPECIFY SLIDE FINISH, BALL BEARING MATERIAL AND INDICATE -L FOR LEFT HAND SLIDE, -R FOR RIGHT HAND SLIDE OR -P FOR A PAIR OF SLIDES AS SHOWN BELOW:



- 2. FINISH: CHANNELS ARE ANODIZED PER MIL-A-8625 TYPE II, CLASS 2, COLOR: BLACK OR TYPE II, CLASS I (CLEAR). CRES PARTS ARE PASSIVATED PER SAE-AMS-2700
- 1. MATERIALS: SLIDE CHANNELS ARE FABRICATED FROM HIGH STRENGTH ALUMINUM ALLOYS COMPONENT PART ARE FABRICATED FROM HIGH STRENGTH ALUMINUM ALLOYS AND CORROSION RESISTANT STEEL. BALLS ARE 440 CRES OR ACETAL. BUMPER IS SANTOPRENE (T.P.E.) REAR STOP BUMPER IS NEOPRENE 80A



SERIES PART NUMBER	SLIDE LENGTH	SLIDE TRAVEL	MOUNTING HOLE PATTERN															LOAD RATING (LBS) PER PAIR	SLIDE WEIGHT CRES BALLS (LBS)	SLIDE WEIGHT ACETAL BALLS (LBS)
			CABINET SECTION							CHASSIS SECTION										
	L	T	A	B	C	D	E	F	G	H	J	K	M	N	R	S	U			
ES380T	10	10.00	-	-	-	4.250	-	-	-	6.500	-	-	-	-	-	-	8.625	250	1.11	0.97
ES380T	12	12.00	-	-	3.250	5.250	7.250	-	-	8.500	-	-	-	-	-	-	10.625	270	1.33	1.17
ES380T	14	14.00	-	-	3.250	6.250	9.250	-	-	10.500	-	-	-	-	-	-	12.625	250	1.55	1.36
ES380T	16	16.00	-	-	4.250	7.250	10.250	-	-	12.500	12.000	-	-	-	-	-	14.625	220	1.78	1.56
ES380T	18	18.00	-	-	5.250	8.250	11.250	-	-	14.500	12.000	15.000	-	-	-	-	16.250	170	2.00	1.75
ES380T	20	20.00	-	3.250	6.250	9.250	12.250	15.250	-	16.500	12.000	15.000	-	-	-	-	18.625	140	2.22	1.95
ES380T	22	22.00	-	4.250	7.250	10.250	13.250	16.250	-	18.500	12.000	15.000	18.000	-	-	-	20.625	130	2.44	2.15
ES380T	24	24.00	-	5.250	8.250	11.250	14.250	17.250	-	20.00	12.000	15.000	18.000	21.000	-	-	22.625	120	2.67	2.34
ES380T	26	26.00	3.250	6.250	9.250	12.250	15.250	18.250	21.250	22.500	12.000	15.000	18.000	21.000	-	-	24.625	110	2.89	2.53
ES380T	28	28.00	4.250	7.250	10.250	13.250	16.250	19.250	22.250	24.500	12.000	15.000	18.000	21.000	24.000	-	26.625	100	3.11	2.73
ES380T	30	30.00	5.250	8.250	11.250	14.250	17.250	20.250	23.250	26.500	12.000	15.000	18.000	21.000	24.000	27.000	28.625	90	3.34	2.92



Irvine Technology Center
 410 Exchange, Suite 200
 Irvine, CA 92602
 Tel. (714) 665-4400
 Fax: (714) 368-7002
 Website: www.jonathanengr.com
 Engineer - Production - Integration/ Subassembly - Logistics
 United States - Mexico - China - Taiwan

TOLERANCES UNLESS OTHERWISE NOTED				PART NUMBER : ES380T		DESCRIPTION : ALUMINUM EXECUTIVE STEALTH SERIES ES380T
.XX	.XXX	ANGLES	HOLES	DATE : 12/22/14		
± .01	± .005	± 1°	± .005	SHEET 1 OF 1		COPYRIGHT © 2012 JONATHAN ENGINEERED SOLUTIONS